



CEWELD E DUR 55

TYPE	High efficiency hardfacing elektrode	
ANWENDUNGEN	Pomp bodies, Mixer blades, Agitator arms, Concrete pumps.	
EIGENSCHAFTEN	CEWELD E DUR 55 is a heavy coated high efficiency Hardfacing electrode with 160 % recovery. Suitable for applications subject to strong abrasive wear by minerals	
KLASSIFIKATION	AWS	A 5.13: E FeCr-A1
	EN ISO	14700: E Fe7
	DIN	8555: E 3-UM-50-CKRTZ
	F-nr	71

GEEIGNET FÜR 54-62 HRc, Hardfacing loaders, buckets, pumps, cement crushing equipment, screws, mixers blades etc., excellent abrasion resistance and high wear resistance.

ZULASSUNGEN

SCHWEISSPOSITIONEN



TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%)

C	Mn	Cr	Si
4.5	1	25	1

MECHANISCHE GÜTEWERTE

Heat Treatment	R _{P0.2} (MPa)	R _m (MPa)	A5 (%)	Hardness
As Welded				56 HRc

RÜCKTROCKNUNG 300°C / 2 hr

GAS ACC. EN ISO 14175