





TYPE Nickel iron MIG wire for joining dissimilar materials and cast iron.

APPLICATIONS Suitable for welding stainless steels containing 12-14 Cr. Also for welding mild and low alloy steels

which are exposed to termperatures up to 450C. Cast Iron repairs, rebuilding shafts, wheels, critical

joints between steel and cast iron etc.

PROPERTIES Nickel Iron based filler metal for joint welding and claddings on cast Iron. Very wel suited also for

dissimilar welding between cast iron and high alloyed stainless and heat resistant steels or mild steels. Excellent Weldabillity with extreme crack resistance with a ductile weld deposit. Good welding and wetting characteristics and high resistance against porosity. The weld metal is corrosion and heat resistant. Very well suitable for welding with robotics or automated processes.

CLASSIFICATION AWS A 5.15: E NiFe-CI

EN ISO 1071: SC NiFe-1

W.Nr. 2.4472

SUITABLE FOR Grey cast iron, malleable, nodular : NF A 32-101 : FGL 150, 200, 250, 300, 350, 400. NF A 32-201 :

FGS 370-17, 400-12, 500-7, 600-3, 700-2. NF A 32-702 : MN 350-10, 380-18, 450-6, 350-4, 650-3. DIN 1691 : CG-14, 18, 25, 30. DIN 1693 : GGG-40, 50, 60, 70. DIN 1692 : GTS-35, 45, 55, 65, 70.

APPROVALS

WELDING POSITIONS

PA PB PC PE PF

TYPICAL CHEMICAL ANALYSIS OF THE FILLER

METAL (%)

С	Si	Mn	Р	S	Ni	Fe	Cu
0.015	0.06	0.65	0.003	0.001	55	Rem.	0.01

MECHANICAL PROPERTIES

Heat	R _{P0,2}	Rm	A5	Hardness
Treatment	(MPa)	(MPa)	(%)	
As Welded	350	480	12	195 HB

REDRYING Not required

GAS ACC. EN ISO 14175 11