



CEWELD SP 1.4122

TYPE Solid thermal spray wire containing 17% Chromium

APPLICATIONS Stainless steel shafts, Valves, Clutch surfaces from trucks, Pistons, Bearings, Fan blades etc.

PROPRIÉTÉS Solid spray wire that combines high toughness with very good corrosion resistance, shiny coating with a little higher hardness than SP 1.4115. The spray deposit cannot be machined with normal cutting tools, grinding is possible. Hardness approximately 50 HRc

CLASSIFICATION EN ISO 14919: 5.16
W.Nr. 1.4122

CONVIENT POUR Flame spray, electric spray and high speed flame spray.

AGRÉMENTS

POSITIONS DE SOUDAGE



TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)


Si	Mn	Cr	Fe	C	Ni	Mo
0.9	1	16.5	Rem.	0.35	0.9	1

PROPRIÉTÉS MÉCANIQUES

Heat Treatment	R _{P0,2} (MPa)	R _m (MPa)	A5 (%)	Hardness
As Welded				50 HRc

ETUVAGE Not required

GAS ACC. EN ISO 14175



CEWELD SP 1.4122

SP 1.4122 1,2MM

Packaging	KG/unit	EanCode
BS-300	15	8720663409898

SP 1.4122 1,6MM

Packaging	KG/unit	EanCode
BS-300	15	8720663409904
BS-300	15	8720663409911