



CEWELD 4893 Kb (253MA)

certilas® THE FILLER METAL SPECIALIST

TYPE	Rutile coated electrode for heat resistant stainless steel SMAW welding.								
TOEPASSINGEN	Joining and cladding high heat resistant CrNi-steels of the same kind such as heat treatment equipment and chemical installations.								
EIGENSCHAPPEN	High corrosion resistance and excellent weldability on both AC and DC+. The weld deposit is scale and oxidation resistant up to 950°C. Interpass temperature should be kept below 150°C.								
CLASSIFICATIE	EN ISO 3581-A: E Z 23 10 N R 12 W.Nr. 1.4893 F-nr 5 FM 5								
GESCHIKT VOOR	1.4828, 1.4829, 1.4893, 1.4835, 1.4818, 1.4825, 1.4826, 1.4832, 1.4891, 1.4893 X15CrNiSi 20-23, X12 CrNi 22-12, X8CrNiSiN21-11, X9CrNiSiNCe21-11-2 UNS S30815, AISI 309 (Avesta) alloy 253MA								
GOEDKEURINGEN									
LASPOSITIONS	PA PB PC PD PF								
TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%)	C	Si	Mn	Cr	Ni	Mo	N		
	0.1	1	0.97	22	11	0.1	0.1		
MECHANISCHE WAARDEN	Heat Treatment		R _{P0,2} (MPa)	Rm (MPa)	A5 (%)	Hardness			
	As Welded		360	590	27	HRc			
HERDROGEN	300°C / 2 hr								
GAS ACC. EN ISO 14175									